

G-O Amber Light

■ 09.3201.BZA - Bronze


Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Main specifications

Lamp category	LED	Mountings	Wall recessed
Power (W)	1.2W	Environment	Indoor
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	2		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	72
Beam angle C90-270 (°)	72



Beam Angle:	72°		
h(m)	E(lx)	D(m)	
1	1	1.46	
2	0	2.92	
3	0	4.38	
4	0	5.85	
5	0	7.31	

Luminous flux luminaire
2 lm

Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Remote
Emergency	Without
Insulation class	III

Physical

Color	Bronze
Orientation	Fixed
Recessed depth (mm)	56
Weight (kg)	0.2

Note

Equipment for remote installation in an accesible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

G-O Amber Light




Prepared for recessing
08.8422.00



Dimmable DALI control unit with 1
channel for 24V LED modules. Power
supply not included
60.8635



Electronic transformer with constant
voltage (24V) for LED. 100/240V. 25W
60.8703



Electronic transformer with constant
voltage (24V) for LED. 8W, 110/240V,
50/60H
60.9157