

G-O White Light

09.3200.29A - Anodized Aluminium


Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	1.2W		
CCT (K)	3000K		
Net lumen (lm)	4		
Mountings	Wall recessed		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	74
Beam angle C90-270 (°)	74



Luminous flux lumineuse
4 lm

Beam Angle: 74°		
h(m)	E(lx)	D(m)
1	2	1.51
2	1	3.03
3	0	4.54
4	0	6.06
5	0	7.57

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 1		

Physical

Color	Anodized Aluminium
Orientation	Fixed
Recessed depth (mm)	56
Weight (kg)	0.11

Note

Equipment for remote installation in an accessible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

G-O White Light




Prepared for recessing
08.8422.00



Electronic transformer with constant
voltage (24V) for LED. 100/240V. 25W
60.8703



Dimmable DALI control unit with 1
channel for 24V LED modules. Power
supply not included
60.8635



Electronic transformer with constant
voltage (24V) for LED. 8W, 110/240V,
50/60H
60.9157