

## G-O White Light

09.3200.30A - White


Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Wall recessed
<b>Power (W)</b>	1.2W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	4		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	74
<b>Beam angle C90-270 (°)</b>	74



<b>Beam Angle:</b>	74°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2	1.51	
2	1	3.03	
3	0	4.54	
4	0	6.06	
5	0	7.57	

Luminous flux luminaire  
4 lm

### Electrical

<b>Frequency (Hz)</b>	50/60
<b>Dimmable</b>	Yes
<b>Driver</b>	Remote
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	56
<b>Weight (kg)</b>	0.11

### Note

Equipment for remote installation in an accesible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

## G-O White Light



---

Prepared for recessing  
08.8422.00




---

Dimmable DALI control unit with 1  
channel for 24V LED modules. Power  
supply not included  
60.8635



---

Electronic transformer with constant  
voltage (24V) for LED. 100/240V. 25W  
60.8703



---

Electronic transformer with constant  
voltage (24V) for LED. 8W, 110/240V,  
50/60H  
60.9157