

G-O White Light

■ 09.3200.ANA - Anodized Black


Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Main specifications

Lamp category	LED	Environment	Indoor
Power (W)	1.2W		
CCT (K)	3000K		
Net lumen (lm)	4		
Mountings	Wall recessed		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	74
Beam angle C90-270 (°)	74



Beam Angle:	74°		
h(m)	E(lx)	D(m)	
1	2	1.51	
2	1	3.03	
3	0	4.54	
4	0	6.06	
5	0	7.57	

Luminous flux luminaire
4 lm

Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Remote
Emergency	Without
Insulation class	III

Physical

Color	Anodized Black
Orientation	Fixed
Recessed depth (mm)	56
Weight (kg)	0.11

Note

Equipment for remote installation in an accesible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

G-O White Light



Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60Hz
60.9157



Electronic transformer with constant voltage (24V) for LED. 100/240V, 25W
60.8703



Prepared for recessing
08.8422.00



Dimmable DALI control unit with 1 channel for 24V LED modules. Power supply not included
60.8635