

## Giano Ø 220

■ 09.3001.18B - Dark Brown


Surface signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	212
<b>Lamp category</b>	LED	<b>Mountings</b>	Wall surface
<b>Power (W)</b>	6W	<b>Environment</b>	Indoor dry location, Outdoor wet location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical


<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	68
<b>Beam angle C90-270 (°)</b>	100



Beam Angle: 100°

h(m)	E(lx)	D(m)
1	52	10.35
2	13	20.70
3	6	31.04
4	3	41.39
5	2	51.74

Luminous flux luminaire  
212 lm



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Dark Brown
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.20

