

## Giano Ø100

09.3000.18B - Dark Brown

Recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.


Recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.

### Main specifications

Number of heads	1	Net lumen (lm)	49
Lamp category	LED	Mountings	Wall recessed
Power (W)	1W	Environment	Indoor, Outdoor
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Diffused light
Beam angle (°)	57
Beam angle C90-270 (°)	89



Beam Angle: 89°

h(m)	E(lx)	D(m)
1	16	4.17
2	4	8.34
3	2	12.51
4	1	16.68
5	1	20.86

Luminous flux luminaire  
49 lm


### Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

### Physical

Color	Dark Brown
Orientation	Fixed
Recessed depth (mm)	77
Weight (kg)	0.25

### Certification / Marking



## Giano Ø100



---

Accessory for concrete instalation  
08.8261.00