



Giano Ø100

■ 09.3000.72B - Grey

Recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.


Recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	49
Lamp category	LED	Mountings	Wall recessed
Power (W)	1W	Environment	Indoor, Outdoor
CCT (K)	3000K		
CRI	80		

Optical


Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Diffused light
Beam angle (°)	57
Beam angle C90-270 (°)	89



Beam Angle: 89°

h(m)	E(lx)	D(m)
1	16	4.17
2	4	8.34
3	2	12.51
4	1	16.68
5	1	20.86

Luminous flux luminaire
49 lm




Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Grey
Orientation	Fixed
Recessed depth (mm)	77
Weight (kg)	0.25

Certification / Marking



Giano Ø100



Accessory for concrete instalation
08.8261.00