



### Giano Ø220

■ 09.3001.72B - Grey


Surface signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply included.

#### Main specifications

|                 |       |                |                 |
|-----------------|-------|----------------|-----------------|
| Number of heads | 1     | Net lumen (lm) | 212             |
| Lamp category   | LED   | Mountings      | Wall surface    |
| Power (W)       | 6W    | Environment    | Indoor, Outdoor |
| CCT (K)         | 3000K |                |                 |
| CRI             | 80    |                |                 |

#### Optical


|                        |                  |
|------------------------|------------------|
| Lighting type          | Indirect, Direct |
| LED type               | Power LED        |
| Light distribution     | Asymmetric       |
| Optical type           | Diffused light   |
| Beam angle (°)         | 68               |
| Beam angle C90-270 (°) | 100              |



Beam Angle: 100°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 52    | 10.35 |
| 2    | 13    | 20.70 |
| 3    | 6     | 31.04 |
| 4    | 3     | 41.39 |
| 5    | 2     | 51.74 |

Luminous flux luminaire  
212 lm



#### Electrical

|                |            |                  |   |
|----------------|------------|------------------|---|
| Frequency (Hz) | 50/60      | Insulation class | I |
| Dimmable       | No         |                  |   |
| Driver         | Integrated |                  |   |
| Driver type    | Electronic |                  |   |
| Emergency      | Without    |                  |   |

#### Physical

|             |       |
|-------------|-------|
| Color       | Grey  |
| Orientation | Fixed |
| Weight (kg) | 1.20  |

#### Certification / Marking

