



In-Finity 100 Recessed No Trim Emergency 3000K General Lighting Dali

■ N10NEM3G30BDA - White

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	25.5W/m		
CCT (K)	3000K		
CRI	80		
Mountings	Recessed		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
Emergency	Without		

Physical


Color	White
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	11
Length (mm)	1400

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Recessed No Trim Emergency 3000K General Lighting Dali



Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour White)
08.9054.40

500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0111.00