Indoor dry location







### N10NEM4U30B - White

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Environment

Main specifications	
Lamp category	

LED Power (W) 25.5W/m CCT (K) 4000K CRI 80 Mountings Recessed

# Optical

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light

#### Electrical

Dimmable No Driver Integrated Driver type Non Dimmable Emergency Without Insulation class


## Physical

Color White Orientation Fixed Recessed depth (mm) 135 Weight (kg) 8.20 Length (mm) 1400

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405  $mm.\ In\ normal\ use,\ it\ uses\ the\ same\ power\ consumption\ as\ the\ standard\ In-Flnity.\ In\ emergency\ use,\ it\ emits\ 10\%$ of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

















# In-Finity 100 Recessed No Trim Emergency 4000K Micro-Prismatic Diffuser



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00