In-Finity 100 Recessed Trim 3000K General Lighting

N10T193G02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.





Main specifications

Lamp category	LED	**Mountings**	Recessed
Power (W)	25.5W/m	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	5212		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Luminous flux luminaire
5212 lm

Beam Angle: 103°

h(m)	E(lx)	D(m)
1	1968	2.54
2	492	5.07
3	219	7.61
4	123	10.14
5	79	12.68

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Anodized Grey
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	17.70
Length (mm)	1970

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps

In-Finity 100 Recessed Trim 3000K General Lighting

Metal cover. Recessed Trim. 100 mm
(Colour Black)
08.9055.NS

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0111.00

Metal cover. Recessed Trim. 100 mm
(Colour Anodized Grey)
08.9055.02

Metal cover. Recessed Trim. 100 mm
(Colour White)
08.9055.40