


In-Finity 100 Recessed Trim 4000K General Lighting Dali

■ N10T144G02BDA - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




Main specifications

Lamp category	LED	Mountings	Recessed
Power (W)	25.5W/m	Environment	Indoor
CCT (K)	4000K		
CRI	80		
Net lumen (lm)	4150		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Beam Angle: 103°

h(m)	E(lx)	D(m)
1	1567	2.54
2	392	5.07
3	174	7.61
4	98	10.14
5	63	12.68

Luminous flux luminaire
4150 lm

Electrical

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

Physical

Color	Anodized Grey
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	11
Length (mm)	1405

Certification / Marking



Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.