







In-Finity 100 Recessed Trim 4000K Micro-Prismatic Diffuser Dali

N10T054U14BDA - Black

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

LED type Light distribution Optical type Beam angle (°) Beam angle C90-270	Lamp category Power (W) CCT (K) CRI Net lumen (Im)	LED 25.5W/m 4000K 80 1611	. .	ecessed Idoor dry location
Frequency (Hz) 50/60 Insulation class I Dimmable Yes Driver Integrated Driver type Dimmable DALI 1	Lighting type LED type Light distribution Optical type Beam angle (°)	Top LED Symmetric Diffused light 73	60° 30° 954 cd Luminous flux lumi	$\begin{array}{c ccccc} & & & & & & & \\ \hline 90^{\circ} & & & & & \\ 60^{\circ} & & & & & \\ \hline & & & & & \\ 60^{\circ} & & & & & \\ \hline & & & & & \\ 2 & 238 & 2.95 \\ \hline & & & & & \\ 2 & 238 & 2.95 \\ \hline & & & & & \\ 3 & 106 & 4.42 \\ \hline & & & & \\ 4 & 60 & 5.90 \\ \hline & & & & \\ 30^{\circ} & & & \\ \hline & & & \\ 30^{\circ} & & & \\ \hline \end{array}$
- Without	Frequency (Hz) Dimmable Driver	Yes Integrated Dimmable DALI	Insulation class	

Note

Color

Orientation

Weight (kg)

Length (mm)

Recessed depth (mm)

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Black

Fixed

135

565

4

In-Finity 100 Recessed Trim 4000K Micro-Prismatic Diffuser Dali



Metal cover. Recessed Trim. 100 mm (Colour Black) 08.9055.NS 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal cover. Recessed Trim. 100 mm (Colour Anodized Grey) 08.9055.02



Metal cover. Recessed Trim. 100 mm (Colour White) 08.9055.40