





LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


## Main specifications

Lamp category	LED	Mountings	Recessed
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		

CRI 80 Net lumen (lm) 2375

#### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81




h(m) = E(Ix)D(m) 1406 1.47 2.95 2 351 3 156 4.42 4 88 5.90 5 56 7.37

Beam Angle:

73°

2375 lm





rrequency (HZ)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

## Insulation class















### Physical

Color	Anodized Grey
Orientation	Fixed
Recessed depth (mm)	135
Weight (kg)	5
Length (mm)	845

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405  $mm.\ In\ normal\ use,\ it\ uses\ the\ same\ power\ consumption\ as\ the\ standard\ In-Flnity.\ In\ emergency\ use,\ it\ emits\ 10\%$ of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 100 Recessed Trim 4000K Micro-Prismatic Diffuser



Metal cover. Recessed Trim. 100 mm (Colour Black) 08.9055.NS

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00

Metal cover. Recessed Trim. 100 mm (Colour Anodized Grey) 08.9055.02



Metal cover. Recessed Trim. 100 mm (Colour White) 08.9055.40