




In-Finity 100 Recessed Trim 4000K Micro-Prismatic Diffuser

■ **N10T254U14B - Black**

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




Main specifications

| | | | |
|-----------------------|---------|--------------------|----------|
| Lamp category | LED | Mountings | Recessed |
| Power (W) | 25.5W/m | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 80 | | |
| Net lumen (lm) | 7125 | | |

Optical

| | |
|-------------------------------|----------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 73 |
| Beam angle C90-270 (°) | 81 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 73° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 4217 | 1.47 | |
| 2 | 1054 | 2.95 | |
| 3 | 469 | 4.42 | |
| 4 | 264 | 5.90 | |
| 5 | 169 | 7.37 | |

Luminous flux luminaire
7125 lm

Electrical

| | | | |
|-----------------------|------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Electronic | | |
| Emergency | Without | | |

Physical

| | |
|----------------------------|-------|
| Color | Black |
| Orientation | Fixed |
| Recessed depth (mm) | 135 |
| Weight (kg) | 18.80 |
| Length (mm) | 2530 |

Certification / Marking



Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.