


In-Finity 100 Recessed Trim Emergency 3000K General Lighting

■ N10TEM3G02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



Main specifications

| | | | |
|----------------------|----------|--------------------|---------------------|
| Lamp category | LED | Environment | Indoor dry location |
| Power (W) | 25.5W/m | | |
| CCT (K) | 3000K | | |
| CRI | 80 | | |
| Mountings | Recessed | | |

Optical

| | |
|---------------------------|----------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |

Electrical

| | |
|-------------------------|--------------|
| Dimmable | No |
| Driver | Integrated |
| Driver type | Non Dimmable |
| Emergency | Without |
| Insulation class | I |

Physical

| | |
|----------------------------|---------------|
| Color | Anodized Grey |
| Orientation | Fixed |
| Recessed depth (mm) | 135 |
| Length (mm) | 1400 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps



In-Finity 100 Recessed Trim Emergency 3000K General Lighting



5

Metal cover. Recessed Trim. 100 mm
(Colour White)
08.9055.40



5

Metal cover. Recessed Trim. 100 mm
(Colour Black)
08.9055.NS



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0111.00



5

Metal cover. Recessed Trim. 100 mm
(Colour Anodized Grey)
08.9055.02