

## In-Finity 100 Recessed Trim Emergency 3000K Micro-Prismatic Diffuser Dali

■ N10TEM3U02BDA - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### Main specifications

<b>Lamp category</b>	LED	<b>Environment</b>	Indoor dry location
<b>Power (W)</b>	25.5W/m		
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		
<b>Mountings</b>	Recessed		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light

### Electrical





<b>Dimmable</b>	Yes
<b>Driver</b>	Integrated
<b>Driver type</b>	Dimmable DALI
	1
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	Anodized Grey
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	135
<b>Length (mm)</b>	1400

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



## In-Finity 100 Recessed Trim Emergency 3000K Micro-Prismatic Diffuser Dali



5

---

Metal cover. Recessed Trim. 100 mm  
(Colour Anodized Grey)  
08.9055.02



5

---

Metal cover. Recessed Trim. 100 mm  
(Colour White)  
08.9055.40



5

---

Metal cover. Recessed Trim. 100 mm  
(Colour Black)  
08.9055.NS



---

500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser  
that, thanks to its unique  
microprismatic texture, provides a  
glare free UGR<19 light beam  
08.0114.00