Surface

Indoor dry location







In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali

■ N10S163U14BDA - Black


LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications

Lamp category	LED	Mountings
Power (W)	25.5W/m	Environment
CCT (K)	3000K	
CRI	80	
Net lumen (lm)	4229	

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



h(m) E(lx) D(m) 2503 1.47 2.95 2 626 3 278 4.42 4 156 5.90 5 100 7.37

Beam Angle:

73°

4229 lm

Insulation class

L	



Frequency (Hz) Dimmable	50/60 Yes
Driver	Integrated
Driver type	Dimmable DALI

Without Emergency















Color	Black
Orientation	Fixed
Weight (kg)	16.20
Length (mm)	1690


Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 $mm.\ In\ normal\ use,\ it\ uses\ the\ same\ power\ consumption\ as\ the\ standard\ In-Flnity.\ In\ emergency\ use,\ it\ emits\ 10\%$ of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40