73°

D(m)

1.47 2.95

Beam Angle: h(m) = E(Ix)

2

2942

736







4971

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


## Main specifications

Lamp category	LED	Mountings	Surface
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

### Optical

Net lumen (lm)

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



4971 lm

3 327 4.42 4 184 5.90 5 118 7.37

Electrical

Frequency (Hz)	50/60	Insulation class	- 1
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		

**Emergency** Without


### Physical

White
Fixed
17.70
1970

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405  $mm.\ In\ normal\ use,\ it\ uses\ the\ same\ power\ consumption\ as\ the\ standard\ In-Flnity.\ In\ emergency\ use,\ it\ emits\ 10\%$ of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.







# In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02