





LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


## Main specifications

Lamp category	LED	Mountings	Surtace
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		

CCT (K) 4000K CRI 80 Net lumen (lm) 1611



Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Ream angle C90-270 (°)	81



h(m) E(lx)D(m) 1.47 954 2 2.95 238 3 106 4.42 5.90 60 5 38 7.37

Beam Angle:

73°

Luminous nux lumina
1611 lm

	lectrical
-	I ACT PICA

Driver type

Frequency (Hz)	50/60	Insulation class	- 1
Dimmable	Yes		
Driver	Integrated		

Dimmable DALI

Emergency Without

## Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	4
Length (mm)	565

## Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.





## In-Finity 100 Surface 4000K Micro-Prismatic Diffuser Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02