



# In-Finity 100 Surface 4000K Micro-Prismatic Diffuser

# ■ N10S114U14B - Black

Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main s	pecifications
--------	---------------


•			
Lamp category	LED	Mountings	Surface
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

3167

### Optical

Net lumen (lm)

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



Luminous flux luminaire 3167 lm

Insulation class

Beam Angle:		73°
h(m)	E(lx)	D(m)
1	1874	1.47
2	469	2.95
3	208	4.42
4	117	5.90
5	75	7 37

#### Electrical

rrequency (nz)	30/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

## **Physical**

Color	Black
Orientation	Fixed
Weight (kg)	7.40
Length (mm)	1125

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 100 Surface 4000K Micro-Prismatic Diffuser







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40 Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS