



In-Finity 100 Surface 4000K Micro-Prismatic Diffuser

N10S164U02B - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications

-amp caregory	LLD
Power (W)	25.5W/m
CCT (K)	4000K
CRI	80

LED


Net lumen (lm) 4778

Surface Mountings Environment

Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



Insulation class

h(m)	E(lx)	D(m)
1	2828	1.47
2	707	2.95
3	314	4.42
4	177	5.90
5	113	7.37

Beam Angle:

73°

Electrical

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Physical

Anodized Gre
Fixed
16.20
1690

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Surface 4000K Micro-Prismatic Diffuser








500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40 Metal cover. Surface / Suspension Down. 100 mm 08.9054.06







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS