
2968 Surface

Indoor dry location












## In-Finity 100 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser




LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### Main specifications

Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	25.5W/m	Environment
CCT (K)	3000K	
CDI	90	

#### Optical

Direct
Top LED
Symmetric
Diffused light
73
81



h(m)	E( <b>l</b> ×)	D(m
1	1757	1.47
2	439	2.95
3	195	4.42
4	110	5.90
5	70	7.37

Beam Angle:

73°

2968 lm

-	lectrica

Frequency (Hz)	50/60	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	
Emergency	Without	

## Physical

Color	White
Orientation	Fixed
Weight (kg)	8.20

#### Note

 $Micro-Prismatic \ Diffuser: Highly \ efficient \ multilayer \ diffuser \ that, thanks \ to \ its \ unique \ micro-prismatic \ texture,$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 100 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02