



In-Finity 100 Surface Emergency 4000K General Lighting Dali

■ N10SEM4G14BDA - Black

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	25.5W/m		
CCT (K)	4000K		
CRI	80		
Mountings	Surface		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

Electrical

Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI 1
Emergency	Without
Insulation class	I

Physical

Color	Black
Orientation	Fixed
Weight (kg)	8.20
Length (mm)	1400

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Surface Emergency 4000K General Lighting Dali



5



5

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour Black)
08.9054.NS

500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0111.00

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour White)
08.9054.40



5



5

Metal cover. Surface / Suspension
Down. 100 mm
08.9054.06

Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour Anodized Grey)
08.9054.02