In-Finity 100 Suspension Down 3000K General Lighting Dali

N10D113G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED	**Mountings**	Suspension
Power (W)	25.5W/m	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	3111		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Luminous flux luminaire
3111 lm

Beam Angle: 103°

h(m)	E(lx)	D(m)
1	1175	2.54
2	294	5.07
3	131	7.61
4	73	10.14
5	47	12.68



Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	7.40
Length (mm)	1125

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 3000K General Lighting Dali

Suspension kit
08.0030

Metal cover. Surface / Suspension Down. 100 mm
08.9054.06

Power supply rose. Dali
08.0031.00.DA

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey)
08.9054.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black)
08.9054.NS

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0111.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White)
08.9054.40