



In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser Dali

N10D253U02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications


Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

6677

Optical

Net lumen (lm)

Lighting type
Direct
Top LED
Light distribution
Optical type
Beam angle (°)
Beam angle C90-270 (°)
Direct
Top LED
Symmetric
Optifused light
73
Beam angle C90-270 (°)



Insulation class

Bean	Beam Angle:	
h(m)	E(lx)	D(m
1	3952	1.47
2	988	2.95
3	439	4.42
4	247	5.90
5	158	7.37

F	lectrical

Frequency (Hz)	50/60	
Dimmable	Yes	
Driver	Integrated	
Driver type	Dimmable DALI	
	1	

Emergency Without

Physical


Anodized Grey	
Fixed	
18.80	
2530	

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Power supply rose. Dali 08.0031.00.DA



Suspension kit 08.0030



Metal cover. Surface / Suspension

