


■ N10D253U02B - Anodized Grey

Main specifications

Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	6677		

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



$h(m)$	$E(lx)$	$D(m)$
0	0	0
1	1	1
2	4	4
3	9	9
4	16	16
5	25	25
6	36	36
7	49	49
8	64	64
9	81	81
10	100	100
11	121	121
12	144	144
13	169	169
14	196	196
15	225	225
16	256	256
17	289	289
18	324	324
19	361	361
20	400	400
21	441	441
22	484	484
23	529	529
24	576	576
25	625	625
26	676	676
27	729	729
28	784	784
29	841	841
30	900	900
31	961	961
32	1024	1024
33	1089	1089
34	1156	1156
35	1225	1225
36	1296	1296
37	1369	1369
38	1444	1444
39	1521	1521
40	1600	1600
41	1681	1681
42	1764	1764
43	1849	1849
44	1936	1936
45	2025	2025
46	2116	2116
47	2209	2209
48	2304	2304
49	2401	2401
50	2500	2500
51	2601	2601
52	2704	2704
53	2809	2809
54	2916	2916
55	3025	3025
56	3136	3136
57	3249	3249
58	3364	3364
59	3481	3481
60	3600	3600
61	3721	3721
62	3844	3844
63	3969	3969
64	4096	4096
65	4225	4225
66	4356	4356
67	4489	4489
68	4624	4624
69	4761	4761
70	4900	4900
71	5041	5041
72	5184	5184
73	5329	5329
74	5476	5476
75	5625	5625
76	5776	5776
77	5929	5929
78	6084	6084
79	6241	6241
80	6400	6400
81	6561	6561
82	6724	6724
83	6889	6889
84	7056	7056
85	7225	7225
86	7396	7396
87	7569	7569
88	7744	7744
89	7921	7921
90	8100	8100
91	8281	8281
92	8464	8464
93	8649	8649
94	8836	8836
95	9025	9025
96	9216	9216
97	9409	9409
98	9604	9604
99	9801	9801
100	10000	10000

1	3952	1.47
2	988	2.95
3	439	4.42
4	247	5.90
5	158	7.37

Luminous flux lumineire
6677 lm

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	18.80
Length (mm)	2530

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19° light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 3000K Micro-Prismatic Diffuser



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey)
08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black)
08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam
08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White)
08.9054.40



Suspension kit
08.0030



Metal cover. Surface / Suspension Down. 100 mm
08.9054.06



Power supply rose

