



In-Finity 100 Suspension Down 4000K General Lighting Dali

N10D054G02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.


Main specifications

| Lamp category | LED |
|----------------|---------|
| Power (W) | 25.5W/m |
| CCT (K) | 4000K |
| CRI | 80 |
| Net lumen (lm) | 1689 |

Mountings Environment Suspension Indoor dry location










| ighting type | Direct |
|------------------------|----------------|
| .ED type | Top LED |
| ight distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 103 |
| Beam angle C90-270 (°) | 107 |
| - | |



Luminous flux luminaire 1689 lm

| Beam Angle: | | 103° |
|-------------|-------|-------|
| h(m) | E(lx) | D(m) |
| 1 | 638 | 2.54 |
| 2 | 160 | 5.07 |
| 3 | 71 | 7.61 |
| 4 | 40 | 10.14 |
| 5 | 26 | 12.68 |

Electrical

Optical

| Frequency (Hz) | 50/60 | Insulation class | - 1 |
|----------------|---------------|------------------|-----|
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |
| Emergency | Without | | |

Physical

| Color | Anodized Grey |
|-------------|---------------|
| Orientation | Fixed |
| Weight (kg) | 4 |
| Length (mm) | 565 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K General Lighting Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room

