



In-Finity 100 Suspension Down 4000K General Lighting Dali

N10D054G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	25.5W/m
CCT (K)	4000K
CRI	80
Net lumen (lm)	1689

Mountings Environment

Suspension Indoor dry location

Beam Angle: 103°

E(lx)

638

160

71

D(m)

2.54

5.07

7.61


h(m)

2

3



Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 103 Beam angle C90-270 (°) 107



4 40 10.14 26 12.68

Luminous flux luminaire 1689 lm



Electrical Frequency (Hz)

Dimmable Yes Integrated Driver Dimmable DALI Driver type

Without

50/60

Insulation class



Emergency Physical

Color	White
Orientation	Fixed
Weight (kg)	4
Lenath (mm)	565

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K General Lighting Dali



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm opal diffuser. Diffuse, glare

free and uniform lighting throughout



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Suspension kit 08.0030



Metal cover. Surface / Suspension

Down. 100 mm 08.9054.06

the room 08.0111.00