



In-Finity 100 Suspension Down 4000K General Lighting Dali

■ N10D144G14BDA - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	25.5W/m
CCT (K)	4000K
CRI	80
Net lumen (lm)	4150

Mountings Environment


Suspension Indoor dry location





Optical

Direct Top LED Symmetric Diffused light 103 107



Luminous flux luminaire

Beam Ang l e:		103°
h(m)	E(l x)	D(m
1	1567	2.54
2	392	5.07
3	174	7.61
4	98	10.14
5	63	12 68

4150 lm

-	L	

-	lectrical
_	- Cuicai

uency (Hz)

i i equelicy (i iz)	30/00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
	1

50/60

Emergency Without Insulation class



Physical


Color	Black
Orientation	Fixed
Weight (kg)	11
Length (mm)	1405

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K General Lighting Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Power supply rose. Dali 08.0031.00.DA



Suspension kit 08.0030



Metal cover. Surface / Suspension

Down. 100 mm 08.9054.06