



In-Finity 100 Suspension Down 4000K General Lighting

N10D114G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	25.5W/m
CCT (K)	4000K
CRI	80
Net lumen (lm)	3320

Mountings Environment

Suspension Indoor dry location






L	



•	
Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Insulation class

E(lx) h(m) D(m) 1254 2.54 2 313 5.07 3 139 7.61 4 78 10.14 50 12.68

Beam Angle: 103°

Electrical Fraguency (Hz)

Optical

rrequericy (112)	30/00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

50/60

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	7.40
Length (mm)	1125

Note

 $Opal\ Diffuser:\ Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K General Lighting



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White)

