

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali

■ N10D084U30BDA - White


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

| | | | |
|-----------------------|---------|--------------------|---------------------|
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 25.5W/m | Environment | Indoor dry location |
| CCT (K) | 4000K | | |
| CRI | 80 | | |
| Net lumen (lm) | 2375 | | |

Optical

| | |
|-------------------------------|----------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 73 |
| Beam angle C90-270 (°) | 81 |



Beam Angle: 73°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1406 | 1.47 |
| 2 | 351 | 2.95 |
| 3 | 156 | 4.42 |
| 4 | 88 | 5.90 |
| 5 | 56 | 7.37 |

Luminous flux luminaire
2375 lm

Electrical

| | | | |
|-----------------------|---------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------|
| Color | White |
| Orientation | Fixed |
| Weight (kg) | 5 |
| Length (mm) | 845 |

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali



Suspension kit
08.0030



Metal cover. Surface / Suspension
Down. 100 mm
08.9054.06



Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour White)
08.9054.40



Metal End Cap. Recessed No Trim /
Surface / Suspension Down. 100 mm
(Colour Black)
08.9054.NS



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0114.00



Power supply rose. Dali
08.0031.00.DA



Metal End Cap. Recessed No Trim /

(Colour Anodized Grey)

08.9054.02