



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali

■ N10D114U14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		
Net lumen (lm)	3167		

Optical

Lighting type
Direct
Top LED
Light distribution
Optical type
Beam angle (°)
Beam angle C90-270 (°)
Direct
Top LED
Symmetric
Optifused light
73
Beam angle C90-270 (°)



3167 lm

***	3	208	4.42
	4	117	5.90
$\sqrt{1874} \text{ cd} \sqrt{30^\circ}$	5	75	7.37
nous flux luminaire			

73°

D(m)

1.47

2.95

Beam Angle:

h(m) = E(Ix)

1874

469

actrica
lectrica

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Dimmable DALI	

Emergency With

Physical

Color	Black
Orientation	Fixed
Weight (kg)	7.40
Length (mm)	1125

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali



FLOS 5



Suspension kit 08.0030

Metal cover. Surface / Suspension Down. 100 mm 08.9054.06

Power supply rose. Dali 08.0031.00.DA







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm

