



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser ■ N10D054U14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED
Power (W)	25.5W/m
CCT (K)	4000K
CRI	80
Net lumen (lm)	1611

Mountings Environment Suspension Indoor dry location










Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Beam angle (°) Diffused light 73 Beam angle C90-270 (°) 81



Luminous flux luminaire 1611 lm

Insulation class

Beam Angle:		73°
h(m)	E(lx)	D(m
1	954	1.47
2	238	2.95
3	106	4.42
4	60	5.90
5	38	7.37

Electrical

Optical

i requericy (112)	30/00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

50/60

Physical


Color	Black
Orientation	Fixed
Weight (kg)	4
Length (mm)	565

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser







Suspension kit 08.0030



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim /

(Colour Black) 08.9054.NS			