


■ N10D144U02B - Anodized Grey

Main specifications

Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		
Net lumen (lm)	3958		

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	73
Beam angle C90-270 (°)	81



$h(m)$	$E(lx)$	$D(m)$
0	0	0
1	0.5	0.5
2	0.8	0.8
3	0.9	0.9
4	0.95	0.95
5	0.98	0.98
6	0.99	0.99
7	0.995	0.995
8	0.998	0.998
9	0.999	0.999
10	1.0	1.0

1	2343	1.47
2	586	2.95
3	260	4.42
4	146	5.90
5	94	7.37

Luminous flux lumineuse
3958 lm

Frequency (Hz)	50/60
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	With

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	11
Length (mm)	1405

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flint. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey)
08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black)
08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam
08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White)
08.9054.40



Suspension kit
08.0030



Metal cover. Surface / Suspension Down. 100 mm
08.9054.06



Power supply rose

