



In-Finity 100 Suspension Down Emergency 3000K Micro-Prismatic Diffuser Dali

■ **N10DEM3U14BDA - Black**

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Lamp category	LED	Environment	Indoor
Power (W)	25.5W/m		
CCT (K)	3000K		
CRI	80		
Mountings	Suspension		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

Electrical

Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

Physical

Color	Black
Orientation	Fixed
Length (mm)	1400

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Certification / Marking

