









In-Finity 100 Suspension Down Emergency 4000K Micro-Prismatic Diffuser Dali

N10DEM4U30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications			
Lamp category Power (W) CCT (K) CRI Mountings	LED 25.5W/m 4000K 80 Suspension	Environment	Indoor dry location
Optical			
Lighting type LED type Light distribution Optical type	Direct Top LED Symmetric Diffused light		
Electrical			
Dimmable Driver Driver type	Yes Integrated Dimmable DALI 1		
Emergency Insulation class	Without		
	ļ		
Physical	1		

Note

Length (mm)

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

1400

In-Finity 100 Suspension Down Emergency 4000K Micro-Prismatic Diffuser Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Power supply rose. Dali 08.0031.00.DA



Suspension kit 08.0030



Metal cover. Surface / Suspension

