

### ■ N10DFC3G02BDA - Anodized Grey


 ${\sf LED\ modular\ system\ for\ suspended\ installation, including\ LED\ luminaires, aluminum\ installation\ profile, and}$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

#### Main specifications

Number of heads	1	Net lumen (lm)	3111
Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

#### Optical

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 103 Beam angle C90-270 (°) 107



Luminous flux luminaire

Beam Angle:		103°
h(m)	E(lx)	D(m)
1	1175	2.54
2	294	5.07
3	131	7.61
4	73	10.14
5	47	12.68

#### **Electrical**

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	

Without


Dimmable DALI Driver type


# **Emergency** Physical

Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	8.20	

### Note

 $Opal\ Diffuser:\ Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.








## In-Finity 100 Suspension Down Flat Corner 3000K General Lighting Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40



Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Power supply rose. Dali 08.0031.00.DA