

In-Finity 100 Suspension Down Flat Corner 3000K General Lighting Dali

N10DFC3G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads	1	Net lumen (lm)	3111
Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	3000K		-
CRI	80		

Optical


Electrical

Frequency (Hz) Dimmable Driver Driver type Emergency

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Direct Top LED Symmetric Diffused light 103 107

Fixed

8.20



Bear	n Ang l e:	103°
h(m)	E(İ x)	D(m)
1	1175	2.54
2	294	5.07
3	131	7.61
4	73	10.14
5	47	12.68

3111 lm

50/60 Yes Integrated Dimmable DALI 1 Without	Insulation class

Note

Physical


Orientation

Weight (kg)

Color

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.







In-Finity 100 Suspension Down Flat Corner 3000K General Lighting Dali



Power supply rose. Dali 08.0031.00.DA

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02

5



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour White) 08.9054.40 Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06