





In-Finity 100 Suspension Down Flat Corner 4000K General **Lighting Dali**

N10DFC4G30BDA - White


 ${\sf LED\ modular\ system\ for\ suspended\ installation, including\ LED\ luminaires, aluminum\ installation\ profile, and}$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads	1	Net lumen (lm)	3320
Lamp category	LED	Mountings	Suspension
Power (W)	25.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 103 Beam angle C90-270 (°) 107



Luminous flux luminaire 3320 lm

Beam Angle:		103°
h(m)	E(lx)	D(m)
1	1254	2.54
2	313	5.07
3	139	7.61
4	78	10.14
5	50	12 68

Electrical

Frequency (Hz) Dimmable	50/60 Yes	Insulation class	I
Driver	Integrated		

Without

Dimmable DALI Driver type

Emergency Physical

Color	White
Orientation	Fixed
Weight (kg)	8.20

EHE CE RETILAP

Note

 $Opal\ Diffuser:\ Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Down Flat Corner 4000K General Lighting Dali





Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Anodized Grey) 08.9054.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 100 mm (Colour Black) 08.9054.NS

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00



Metal End Cap. Recessed No Trim /

Surface / Suspension Down. 100 mm

(Colour White)

08.9054.40



Suspension kit 08.0030



Metal cover. Surface / Suspension Down. 100 mm 08.9054.06



Power supply rose. Dali 08.0031.00.DA