

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali

■ **N10U163G02BDA - Anodized Grey**


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	6106
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Luminous flux luminaire
6106 lm

Beam Angle DIR: 103°

h(m)	E(lx)	D(m)
1	1675	2.54
2	419	5.07
3	186	7.61
4	105	10.14
5	67	12.68

Electrical

Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	16.20
Length (mm)	1690

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali



Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



Power supply rose. Dali
08.0031.00.DA



Suspension kit
08.0030



Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS



Metal cover. Suspension Up & Down.
100 mm
08.9058.06



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0111.00