



■ N10U193G14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	7282
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Luminous flux lumineuse
7282 lm

Beam Angle DIR: 103°

h(m)	E(lx)	D(m)
1	1997	2.54
2	499	5.07
3	222	7.61
4	125	10.14
5	80	12.68

Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Dimmable DALI	
	1	
Emergency	Without	

Physical

Color	Black
Orientation	Fixed
Weight (kg)	17.70
Length (mm)	1970

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali



5

Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0111.00



5

Metal cover. Suspension Up & Down.
100 mm
08.9058.06



5

Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



Suspension kit
08.0030



Power supply rose. Dali
08.0031.00.DA



5

Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS