

■ N10U253G02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

| | | | |
|-----------------|---------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 9334 |
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 38.5W/m | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 103 |
| Beam angle C90-270 (°) | 107 |



Luminous flux lumineuse
9334 lm

Beam Angle DIR: 103°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 2560 | 2.54 |
| 2 | 640 | 5.07 |
| 3 | 284 | 7.61 |
| 4 | 160 | 10.14 |
| 5 | 102 | 12.68 |

Electrical

| | | |
|-----------------------|---------------|-------------------------|
| Frequency (Hz) | 50/60 | Insulation class |
| Dimmable | Yes | |
| Driver | Integrated | |
| Driver type | Dimmable DALI | |
| | 1 | |
| Emergency | Without | |

Physical

| | |
|-------------|---------------|
| Color | Anodized Grey |
| Orientation | Fixed |
| Weight (kg) | 18.80 |
| Length (mm) | 2530 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali



5

Metal cover. Suspension Up & Down.
100 mm
08.9058.06



Power supply rose. Dali
08.0031.00.DA



5

Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS



5

Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



500 mm opal diffuser. Diffuse, glare
free and uniform lighting throughout
the room
08.0111.00



5

Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



Suspension kit
08.0030