

## In-Finity 100 Suspension Up & Down 3000K General Lighting

■ N10U253G14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

## Main specifications

Number of heads	1	Net lumen (lm)	9334
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

## Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Beam Angle DIR: 103°

h(m)	E(lx)	D(m)
1	2560	2.54
2	640	5.07
3	284	7.61
4	160	10.14
5	102	12.68

Luminous flux lumineuse  
9334 lm

## Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>
<b>Dimmable</b>	Yes	
<b>Driver</b>	Integrated	
<b>Driver type</b>	Dimmable DALI	
	1	
<b>Emergency</b>	Without	

## Physical

Color	Black
Orientation	Fixed
Weight (kg)	18.80
Length (mm)	2530

### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 100 Suspension Up & Down 3000K General Lighting Dali



5

Metal cover. Suspension Up & Down.  
100 mm (Colour Anodized Grey)  
08.9058.02



500 mm opal diffuser. Diffuse, glare  
free and uniform lighting throughout  
the room  
08.0111.00



5

Metal cover. Suspension Up & Down.  
100 mm  
08.9058.06



5

Metal cover. Suspension Up & Down.  
100 mm (Colour White)  
08.9058.40



Suspension kit  
08.0030



Power supply rose. Dali  
08.0031.00.DA



5

Metal cover. Suspension Up & Down.  
100 mm (Colour Black)  
08.9058.NS