

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali

N10U253G30BDA - White


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main	specifications
NUSIN	COOCITICATIONC

main opecifications				
Number of heads	1	Net lumen (lm)	9334	
Lamp category	LED	Mountings	Suspension	
Power (W)	38.5W/m	Environment	Indoor dry location	
CCT (K)	3000K			
CRI	80			

Optical

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Indirect, Direct Top LED Symmetric Diffused light 103 107



Beam Angle DIR: 103°					
h(m)	E(I x)	D(m)			
1	2560	2.54			
2	640	5.07			
3	284	7.61			
4	160	10.14			
5	102	12.68			

9334 lm

Electrical			
Frequency (Hz) Dimmable Driver Driver type	50/60 Yes Integrated Dimmable DALI 1	Insulation class	1
Emergency	Without		
Physical			
Color	White		
Orientation	Fixed		
Weight (kg)	18.80		
Length (mm)	2530		

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali




500 mm opal diffuser. Diffuse, glare

the room 08.0111.00

free and uniform lighting throughout



Metal cover. Suspension Up & Down. 100 mm 08.9058.06



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40





Suspension kit 08.0030 Power supply rose. Dali 08.0031.00.DA



Metal cover. Suspension Up & Down. 100 mm (Colour Black) 08.9058.NS