







## In-Finity 100 Suspension Up & Down 3000K General Lighting Dali

## N10U30B3G14BDA - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 38.5W/m 3000K 80	Mountings Environment	Suspension Indoor dry location
Optical Lighting type LED type Light distribution Optical type	Indirect, Direct Top LED Symmetric Diffused light		
Electrical Frequency (Hz) Dimmable Driver Driver type Emergency	50/60 Yes Integrated Dimmable DALI 1 Without	Insulation class	1
Physical Color Orientation Weight (kg) Length (mm)	Black Fixed 21.40 3095		

## Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 100 Suspension Up & Down 3000K General Lighting Dali



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00 Metal cover. Suspension Up & Down. 100 mm 08.9058.06



Metal cover. Suspension Up & Down. 100 mm (Colour Black) 08.9058.NS

5



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02



Suspension kit 08.0030



Power supply rose. Dali 08.0031.00.DA