



## In-Finity 100 Suspension Up & Down 3000K General Lighting

### ■ N10U14B3G14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

#### Main specifications

|                 |         |             |                     |
|-----------------|---------|-------------|---------------------|
| Number of heads | 1       | Mountings   | Suspension          |
| Lamp category   | LED     | Environment | Indoor dry location |
| Power (W)       | 38.5W/m |             |                     |
| CCT (K)         | 3000K   |             |                     |
| CRI             | 80      |             |                     |

#### Optical

|                    |                  |
|--------------------|------------------|
| Lighting type      | Indirect, Direct |
| LED type           | Top LED          |
| Light distribution | Symmetric        |
| Optical type       | Diffused light   |

#### Electrical

|                |              |                  |   |
|----------------|--------------|------------------|---|
| Frequency (Hz) | 50/60        | Insulation class | I |
| Dimmable       | No           |                  |   |
| Driver         | Integrated   |                  |   |
| Driver type    | Non Dimmable |                  |   |
| Emergency      | Without      |                  |   |

#### Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Orientation | Fixed |
| Weight (kg) | 11    |
| Length (mm) | 1405  |

#### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



# In-Finity 100 Suspension Up & Down 3000K General Lighting



Power supply rose  
08.0031.00



Metal cover. Suspension Up & Down.  
100 mm (Colour Anodized Grey)  
08.9058.02



500 mm opal diffuser. Diffuse, glare  
free and uniform lighting throughout  
the room  
08.0111.00



Metal cover. Suspension Up & Down.  
100 mm  
08.9058.06



Metal cover. Suspension Up & Down.  
100 mm (Colour White)  
08.9058.40



Suspension kit  
08.0030



Metal cover. Suspension Up & Down.  
100 mm (Colour Black)  
08.9058.NS