



# In-Finity 100 Suspension Up & Down 3000K General Lighting

## N10U193G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### Main specifications

Number of heads	1
Lamp category	LED
Power (W)	38.5W/m
CCT (K)	3000K
CRI	80


Net lumen (lm) Mountings Environment

7282 Suspension Indoor dry location












## Optical

Lighting type	Indirect, Direc
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	103
Beam angle C90-270 (°)	107



Luminous flux luminaire 7282 lm

Insulation class

Beam Angle DIR: 103°		
h(m)	E( <b>l</b> ×)	D(m
1	1997	2.54
2	499	5.07
3	222	7.61
4	125	10.14
5	80	12.69

#### Electrical

i requericy (112)	30/00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable
Emergency	Without

50/60

## **Physical**

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	17.70
Length (mm)	1970

## Note

 $Opal\,Diffuser:\,Diffuse,\,glare\,free\,and\,uniform\,lighting\,throughout\,the\,room.\,/\,Emergency:\,Emergency\,Module\,And Control of Control$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 100 Suspension Up & Down 3000K General Lighting



FLOS 5



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00

Metal cover. Suspension Up & Down. 100 mm 08.9058.06

Suspension kit 08.0030



Metal cover. Suspension Up & Down.

100 mm (Colour Black)

08.9058.NS

5



Power supply rose 08.0031.00



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40