

## In-Finity 100 Suspension Up & Down 3000K General Lighting

■ N10U30B3G30B - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

### Main specifications

Number of heads	1	Mountings	Suspension
Lamp category	LED	Environment	Indoor dry location
Power (W)	38.5W/m		
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

### Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

### Physical

Color	White
Orientation	Fixed
Weight (kg)	21.40
Length (mm)	3095

### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



# In-Finity 100 Suspension Up & Down 3000K General Lighting



Suspension kit  
08.0030



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0111.00



Metal cover. Suspension Up & Down.  
100 mm (Colour White)  
08.9058.40



Power supply rose  
08.0031.00



Metal cover. Suspension Up & Down.  
100 mm (Colour Anodized Grey)  
08.9058.02



Metal cover. Suspension Up & Down.  
100 mm  
08.9058.06



Metal cover. Suspension Up & Down.  
100 mm (Colour Black)  
08.9058.NS