









In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali

N10U14B3U02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main	spe	citica	itions
------	-----	--------	--------

 Number of heads
 1
 Mountings
 Suspension

 Lamp category
 LED
 Environment
 Indoor dry location

 Power (W)
 38.5W/m

 Power (W)
 38.5W/r

 CCT (K)
 3000K

 CRI
 80

Optical

Lighting typeIndirect, DirectLED typeTop LEDLight distributionSymmetricOptical typeDiffused light

Electrical

Frequency (Hz) 50/60 Insulation class I Dimmable Yes

Driver Integrated
Driver type Dimmable DALI

Emergency Without

Physical

 Color
 Anodized Grey

 Orientation
 Fixed

 Weight (kg)
 11

 Length (mm)
 1405

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser Dali



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00 Metal cover. Suspension Up & Down. 100 mm 08.9058.06



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40



Suspension kit 08.0030



Power supply rose. Dali 08.0031.00.DA



Metal cover. Suspension Up & Down. 100 mm (Colour Black)

